

EASY ROLLER® 14

OPENS DOORS UP TO 14' HIGH



Your 'go to' rolling sheet door operator.

The EasyRoller builds on decades of innovation to deliver a slim, reliable and secure operator, suitable for both residential and commercial rolling sheet door applications.

Featuring a strong 600N DC motor, EasyRoller 14 is designed to reliably lift and lower standard carport and dock sheet doors up to 242lbs (14ft). The opener comes with TrioCode™128 Remote Controls and a bright LED courtesy light for convenience. EasyRoller 14 features soft start-and-stop functionality reducing door stress and damage, helping it last longer.

WHAT'S INCLUDED:



Operator with LED Courtesy Light



Wireless wall button + 2x TrioCode™ 128 Remote Controls



Wall Station



Door drum adapters



Wired Safety Beams

AT A GLANCE:

SECURE & RELIABLE TRANSMITTERS

The TrioCode™128 transmitter system ensures secure and reliable access. It transmits on three frequencies to defeat radio interference, and uses a 128-bit encryption protocol for the ultimate in security.



KEY FEATURES

- 600N DC Motor
- Soft Start / Soft Stop
- Slim fit design
- LED Courtesy Light
- Intelligent Safety System

ADAPTERS AVAILABLE TO SUIT DIFFERENT DOOR TYPES

Operator comes with adaptors for most sheet door drum types as well as an optional Live Axle Kit to suit live axle doors.

SOFT START / SOFT STOP

The Soft Start / Soft Stop feature ramps speed up and down at the start and end of each cycle to reduce stress on the door and opener.

INTELLIGENT SAFETY SYSTEM

If contact is made or an obstruction is detected while moving, the opener either stops and reverses the door to reduce the risk of injury or property damage.

TECHNICAL SPECIFICATIONS



EASYROLLER 14

Power	Input Voltage	120 Vac / 60Hz
	Stand By Power	2.2W
	Motor Type	24V d.c. Permanent Magnet
	Motor Power	100W
Installation^{1,2}	Door Size (approx.)	180 ft ²
	Door Height (max) ³	14 ft
Transmitter System	Receiver/Transmitter Frequency	Multi-frequency UHF FM (434.37, 433.47 & 433.92MHz)
	Coding System	TrioCode™ 128, code hopping
	Code Combinations	3.4x10 ³⁸ code combinations
	Transmitter Capacity (x 4-button registers)	64
Features	Courtesy Light	2 x LED
	Photo Eye Compatibility	2-wire Safety Beams
	Installation	Suits most sheet doors (with adapters)
Optional Accessories	Battery backup	Optional
	Wireless keypad	Optional
	Live axle kit	Optional
	Mini door extension kit	Optional
	HomeLink	Optional
Warranty*	5 years/10,000 cycles on parts 1 year on accessories	

SAFETY & SECURITY FEATURES

- Soft Start/Soft Stop (inverter units only)
- Door Profiling
- TrioCode™128
- Intelligent Safety System

POWER & MOUNTING SYSTEM

- DC Motor - 600N

OPERATING MODES

- Service Indicator
- LED Courtesy Light Output
- Auto Close
- Vacation Mode
- Auxiliary Output

OPTIONS AND UPGRADES




WIRELESS KEYPAD
Weather resistant, secure access without a transmitter or keys. Great for sheds, storage, carports, commercial buildings.



BATTERY BACKUP
In the event of power failure, your rolling sheet door will continue to operate.



MINI DOOR EXTENSION KIT



LIVE AXLE KIT



- Suitable for use on dead axle doors only and windy conditions may trigger the obstruction feature on the opener.
- See full warranty terms and conditions on our website. This brochure is not evidence of our warranty. Our warranty is in addition to any consumer guarantees that may apply under American Law.
- Typical sheet door opening heights: 9.5" drum = 12' / 12" drum = 14'

For more product information, visit www.automatictechnology.com

©2025 Automatic Technology America LLC. The Automatic Technology logos, feature icons, Easy Roller & TrioCode™ are registered trademarks. In an ongoing commitment to product quality, the specifications may change from time to time – E&OE Automatic Technology LLC, 28610 US-290 Suite F09-345, Cypress, TX 77433, United States, www.automatictechnology.com, 1-800-934-9892. *Please see full warranty terms and conditions at www.automatictechnology.com. Date: August 2025



automatic
TECHNOLOGY®